

Dry Container General Specifications

WEIGHT & PAYLOAD	20 FT	40 FT	40 FT High Cube
Maximum Gross Weight	30,480 kg 67,200 lb	32,500 kg 71,650 lb	32,500 kg 71,650 lb
Maximum Payload	28,380 kg 62,570 lb	29,000 kg 63,930 lb	28,800 kg 63,490 lb
Tare Weight	2,100 kg 4,630 lb	3,500 kg 7,720 lb	3,700 kg 8,160 lb
EXTERNAL DIMENSIONS	20 FT	40 FT	40 FT High Cube
Length	6,058 mm 19'10.5"	12,192 mm 40'0"	12,192 mm 40'0"
Width	2,438 mm 8'0"	2,438 mm 8'0"	2,438 mm 8'0"
Height	2,591 mm 8'6"	2,591 mm 8'6"	2,896 mm 9'6"
INTERNAL DIMENSIONS	20 FT	40 FT	40 FT High Cube
Length	5,898 mm 19'4"	12,032 mm 39'6"	12,032 mm 39'6"
Width	2,352 mm 7'9"	2,352 mm 7'9"	2,352 mm 7'9"
Height	2,393 mm 7'10"	2,393 mm 7'10"	2,698 mm 8'10"
DOOR OPENING	20 FT	40 FT	40 FT High Cube
Width	2,340 mm 7'8"	2,340 mm 7'8"	2,340 mm 7'8"
Height	2,280 mm 7'6"	2,280 mm 7'6"	2,585 mm 8'6"
CUBIC CAPACITY	20 FT	40 FT	40 FT High Cube
Internal	33.2 m ³ 1,170 ft ³	67.7 m ³ 2,390 ft ³	76.4 m ³ 2,700 ft ³
TEST LOADS	20 FT	40 FT	40 FT High Cube
Stacking (per post)	97,200 kg 214,290 lb	97,200 kg 214,290 lb	97,200 kg 214,290 lb
Floor Strength	7,260 kg 16,000 lb	7,260 kg 16,000 lb	7,260 kg 16,000 lb

General specifications for reference only. Please contact us for more details.